



Shuangshi Housewrap

Shuangshi HouseWrap is manufactured from a polypropylene woven fabric with a polypropylene coating that contains UV inhibitors.

PRODUCT FEATURES & BENEFITS

- Provides protection from water infiltration but breathes allowing water vapor to escape
- Light weight and somewhat translucent to allow for easy installation
- UV resistant and can be left exposed for up to 6 months
- Tear resistant reduces jobsite waste and blow-offs
- Meets and exceeds all current building codes for water resistive barrier as well as air barrier

PRODUCT SPECIFICATIONS			TEST METHOD	ROLL SIZE	ROLLS PER PALLET
Composition	Woven Polypropylene			9' x 100'	50
Weight per Roll	13.1 lbs. / MSF			9' x 150'	45
Thickness	5.5 mils.			9' x 195'	40
Tensile Strength	MD	79	ASTM D5034	10' x 100'	50
	CD	51		10' x 150'	45
Tear Strength	MD	47.1	ASTM D4533	10' x 195'	40
	CD	18.7		54" x 100'	100
Water Resistance	Pass		ASTM D779	54" x 150'	90
MVTR / Perms	9 Perms		ASTM E96	54" x 195'	80
Fire Rating	Class A		ASTM E84	36" x 100'	150
				36" x 150'	135